



Skill path SD102KS - silver

Product type SD-102KS-10

Basic information

Age category	2 - 10 years
Minimum area	9,3 m x 9,4 m
Equipment measurements	6,3 m x 5,81 m x 2,1 m
Free fall height:	1 m
Load capacity:	1080 kg
Max. number of users:	20
Fall zone: EN 1177	Grass surface
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 11

Material

Wooden units - water-proof plywood
 Metal units - structural steel
 Plastic units - HDPE, polyamide
 Ropes and nets - polypropylene with a steel internal core
 Slide - fibreglass
 Tunnel - fibreglass

Finish

Komaxit powder coating
 Hot-dip galvanizing

Description

The support structure of the skill path is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. The support structure of the steps is made of structural steel with a diameter of 89 mm which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. These structures are embedded in a concrete base. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system.

The slide is made of fibreglass. The face of the slide, barriers and the step boards are made of high quality HDPE (high-pressure, full-coloured polyethylene, which is characterised by high colour stability, UV resistance and mainly safety because it is rigid and there is no risk of injury caused by sharp broken fragments). Ropes and nets are made of HERKULES (16 mm polypropylene ropes with inner steel core) and are connected by plastic connectors. The crawler tunnel is made of fibreglass with high UV stability and high colour stability. The platforms are normally made of waterproof plywood designed for outdoor use or of HDPE on the customer's request. All connecting material is zinc or stainless steel coated.

Equipment

We offer two color variants of the support structure - silver and brown.

