



## UNIVERSAL 4U105KW - brown

Product type 4U-105KW-15

### Basic information

Age category	3 - 15 years
Minimum area	7 m x 4 m
Equipment measurements	3,5 m x 1 m x 2,62 m
Free fall height:	1,5 m
Load capacity:	216 kg
Max. number of users:	4
Fall zone: EN 1177	Rubber or gravel, 28 m <sup>2</sup>
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

### Material

Platform - HPL  
Metal units - structural steel  
Plastic units - HDPE  
Slide - fibreglass

### Finish

Duplex powder coated with coat curing  
Hot-dip galvanizing

### Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slide is made from fibreglass. The surface of the slide is made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The platform is made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). All fastening material is galvanized or stainless steel.

### Equipment

Tower, slide, 2x barrier, ladder.

