



## UNIVERSAL 4U112KW - brown

Product type 4U-112KW-10

### Basic information

|                              |                       |
|------------------------------|-----------------------|
| Age category                 | 2 - 15 years          |
| Minimum area                 | 7,3 m x 4 m           |
| Equipment measurements       | 3,78 m x 1 m x 2,12 m |
| Free fall height:            | 1 m                   |
| Load capacity:               | 270 kg                |
| Max. number of users:        | 5                     |
| Fall zone: EN 1177           | Grass surface         |
| Designation:                 | exterior              |
| Availability of spare parts: | supplied by the       |
| Certificate of Compliance:   | ČSN EN 1176 - 1, 2, 3 |

### Material

Platform - HPL  
 Metal units - structural steel  
 Plastic units - HDPE  
 Slide - fibreglass

### Finish

Komaxit powder coating  
 Hot-dip galvanizing

### Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system. The slide is made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The platform is made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). All fastening material is galvanized or stainless steel.

### Equipment

Tower, slide, 2x barrier, sloping ramp with steps and metal handles.

