



## UNIVERSAL 4U225KW - brown

Product type 4U-225KW-10

### Basic information

Age category	2 - 15 years
Minimum area	12,1 m x 7,5 m
Equipment measurements	9,08 m x 3,78 m x 3,13 m
Free fall height:	1 m
Load capacity:	972 kg
Max. number of users:	18
Fall zone: EN 1177	Grass surface
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

### Material

Platform - HPL
Metal units - structural steel
Plastic units - HDPE, polyamide
Slide - fibreglass
Ropes and nets - polypropylene with a steel internal core
Climbing holds - mix of silica sand and epoxy resin
Roofs - HPL

### Finish

Komaxit powder coating
Hot-dip galvanizing

### Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system. The slide is made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The rope bridge is made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core) and is connected with plastic or aluminium joints. The platforms and the sloping climbing wall are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The climbing holds are made from the mix of silica sand and epoxy resin, which ensures long life, colour preservation as well as skin friendly surface. The roofs are made from HPL (High-pressure laminate, which is characterised by high colour stability, UV resistance and water resistance). All fastening material is galvanized or stainless steel.

### Equipment

2x tower, slide, 2x A-shaped roof, metal beam, sloping ramp with steps and metal handles, sloping ladder with metal steps, rope bridge, sloping climbing wall with climbing holds, 2x barrier from HDPE.

