



UNIVERSAL 6U236KW - brown

Product type 6U-236KW-15

Basic information

| | |
|------------------------------|---------------------------------------|
| Age category | 3 - 15 years |
| Minimum area | 11 m x 10,5 m |
| Equipment measurements | 7,72 m x 5,63 m x 3,56 m |
| Free fall height: | 1,5 m |
| Load capacity: | 702 kg |
| Max. number of users: | 13 |
| Fall zone: EN 1177 | Rubber or gravel, 84,5 m ² |
| Designation: | exterior |
| Availability of spare parts: | supplied by the |
| Certificate of Compliance: | ČSN EN 1176 - 1, 2, 3 |

Material

| |
|--------------------------------|
| Platform - HPL |
| Metal units - structural steel |
| Plastic units - HDPE |
| Slide - fibreglass |
| Tunnel - fibreglass |

Finish

| |
|---------------------------------------|
| Duplex powder coated with coat curing |
| Hot-dip galvanizing |

Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life, or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slide is made from fibreglass. The surfaces of the slide, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The platforms are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). Crawl tunnel is made from fibreglass which is UV stable and it is characterised by high colour stability. All fastening material is galvanized or stainless steel.

Equipment

2x tower, roof, slide, crawl tunnel between the towers, 2x ladder, metal beam, 5x barrier from HDPE.

