



Twin chain swing with a slide RH250KR - Red (f.h. 1,5 m)

Product type RH-250KR-15

Basic information

Age category	2 - 15 years
Minimum area	8,4 m x 8,5 m
Equipment measurements	5,4 m x 3,72 m x 2,24 m
Free fall height:	1,5 m
Load capacity:	324 kg
Max. number of users:	6
Fall zone: EN 1177	Rubber or gravel, 52,5 m ²
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2

Material

Metal units - structural steel
Wooden units - water-proof plywood
Plastic units - HDPE
Slide - fibreglass

Finish

Komaxit powder coating
Hot-dip galvanizing

Description

The support structure of the swing is made from structural steel, which is zinc coated and KOMAXIT powder coated according to the RAL colour chart and is fixed in a concrete bed.

The slide is made from fibreglass. The surface of the slide is made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The swings are hung on a metal girder using galvanized chains. The platform is made from water-proof plywood designed for external environment or from HDPE should the client require. All fastening material is galvanized or stainless steel.

Equipment

We offer three color variants of the support structure - red, blue and brown.

