



## Skill path SD105KS - silver

Product type SD-105KS-10

### Basic information

Age category	2 - 10 years
Minimum area	9,5 m x 7,1 m
Equipment measurements	6,5 m x 4,1 m x 2,26 m
Free fall height:	1 m
Load capacity:	810 kg
Max. number of users:	15
Fall zone: EN 1177	Grass surface
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 11

### Material

Wooden units - water-proof plywood  
 Metal units - structural steel  
 Plastic units - polyamide  
 Ropes and nets - polypropylene with a steel internal core

### Finish

Komaxit powder coating  
 Hot-dip galvanizing

### Description

The support structure of the skill path is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. These structures are embedded in a concrete base. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system.

Ropes and nets are made of HERKULES (16 mm polypropylene ropes with inner steel core) and are connected by plastic connectors. The platforms are normally made of waterproof plywood designed for outdoor use or of HDPE on the customer's request. The wobbly beams are hung on a metal support using galvanized chains. All step boards are made of high quality HDPE (high-pressure, full-coloured polyethylene, which is characterised by high colour stability, UV resistance and mainly safety because it is rigid and there is no risk of injury caused by sharp broken fragments). All fastening material is galvanized or stainless steel.

### Equipment

We offer three color variants of the support structure - silver, blue and brown.

