



Train VL110D

Product type VL-110D-10

Basic information

| | |
|------------------------------|--------------------------|
| Age category | 0 - 10 years |
| Minimum area | 8,6 m x 4,1 m |
| Equipment measurements | 5,62 m x 1,17 m x 1,59 m |
| Free fall height: | 0,5 m |
| Load capacity: | 540 kg |
| Max. number of users: | 10 |
| Fall zone: EN 1177 | Grass surface |
| Designation: | exterior |
| Availability of spare parts: | supplied by the |
| Certificate of Compliance: | ČSN EN 1176 - 1 |

Material

Metal units - structural steel
 Wooden units - thick glued wooden supports
 Plastic units - HDPE
 Tunnels - fibreglass

Finish

Impregnation and coating with a triple layer of lacquer
 Komaxit powder coating
 Hot-dip galvanizing

Description

The support structure of the train is made of thick glued wooden supports. This solution ensures maximum protection against cracking, which is common for products made from solid wood. The wooden supports are impregnated and coated with a triple layer of lacquer, which meets the terms and conditions of the EN71/3 Standard (safe for children's toys). The structures are anchored into the ground in steel plates, which are protected against corrosion by hot-dip galvanizing and fixed in a concrete bed. The anchors are fastened to the play unit with bolts and their structure ensures that they are not in direct contact with the ground. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system. All other parts of the play unit are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). Crawl tunnels are made from fibreglass which is UV stable and it is characterised by high colour stability. All fastening material is galvanized or stainless steel.

