



## Drawing board TK100D

Product type TK-100D-10

### Basic information

|                              |                         |
|------------------------------|-------------------------|
| Age category                 | from 0 years            |
| Minimum area                 | 4,3 m x 3,2 m           |
| Equipment measurements       | 1,3 m x 0,12 m x 1,41 m |
| Free fall height:            | 0 m                     |
| Load capacity:               | Not specified           |
| Max. number of users:        | Not specified           |
| Fall zone: EN 1177           | Grass surface           |
| Designation:                 | exterior                |
| Availability of spare parts: | supplied by the         |
| Certificate of Compliance:   | ČSN EN 1176 - 1         |

### Material

Metal parts - structural steel  
 Wooden parts - thick glued wooden supports, water-proof plywood

### Finish

Impregnation and coating with a triple layer of lacquer  
 Duplex powder coated with coat curing  
 Hot-dip galvanizing

### Description

The panel support structure is made from thick glued wooden supports. This solution ensures maximum protection against cracking, which is common for products made from solid wood. The wooden supports are impregnated and coated with a triple layer of lacquer, which meets the terms and conditions of the EN71/3 Standard (safe for children's toys). The structures are anchored into the ground in steel plates, which are protected against corrosion by hot-dip galvanizing and fixed in a concrete bed. The anchors are fastened to the play unit with bolts and their structure ensures that they are not in direct contact with the ground. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion. The drawing area is made from water-proof plywood, which is designed for external use. All fastening material is galvanized or stainless steel.

