



## UNIVERSAL 4U112K-W - metal

Product type 4U-112K-15-W

### Basic information

Age category	3 - 15 years
Minimum area	8,5 m x 4 m
Equipment measurements	4,84 m x 1 m x 2,62 m
Free fall height:	1,5 m
Load capacity:	270 kg
Max. number of users:	5
Fall zone: EN 1177	Rubber or gravel, 34 m <sup>2</sup>
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

### Material

Metal units - structural steel  
Plastic units - HDPE  
Slide - triple-layered fibreglass

### Finish

Duplex powder coated with coat curing  
Hot-dip galvanizing

### Description

The support structure of the tower unit is made of structural steel (metal profile 100 × 100 mm) which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system.

The slide is made from triple-layered fibreglass. The surface of the slide and platform are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). All fastening material is stainless steel.

### Equipment

Tower, slide, 2x metal railing set in a metal frame, sloping ramp with steps and metal handles.

