



Playhouse DO300KS - silver

Product type DO-300KS-10

Basic information

Age category	0 - 10 years
Minimum area	5,1 m x 4,2 m
Equipment measurements	2,08 m x 1,16 m x 1,98 m
Free fall height:	0 m
Load capacity:	324 kg
Max. number of users:	6
Fall zone: EN 1177	Grass surface
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1

Material

Metal units - structural steel
Wooden units - water-proof plywood
Roof - HPL

Finish

Duplex powder coated with coat curing
Hot-dip galvanizing

Description

The support structure of the playhouse is made of structural steel (metal profile 100 x 100 mm) which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. These structures are anchored to concrete footings. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system.

The roof is made from HPL (High-pressure laminate, which is characterised by high colour stability, UV resistance and water resistance). The drawing area and the side walls are made from water-proof plywood, which is designed for external use. All fastening material is galvanized or stainless steel.

Equipment

Roof, 2x side wall, drawing board.

