



UNIVERSAL 4U410D

Product type 4U-410D-10

Basic information

Age category	2 - 15 years
Minimum area	9,2 m x 10,1 m
Equipment measurements	5,78 m x 6,58 m x 3,13 m
Free fall height:	1 m
Load capacity:	2214 kg
Max. number of users:	41
Fall zone: EN 1177	Grass surface
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

Material

Wooden units - thick glued wooden supports
 Metal units - stainless steel
 Ropes and nets - polypropylene with a steel internal core
 Plastic units - HDPE, polyamide
 Slide - fibreglass
 Roofs - HPL

Finish

Impregnation and coating with a triple layer of lacquer
 Duplex powder coated with coat curing
 Hot-dip galvanizing

Description

The tower unit support structure is made from thick glued wooden supports. This solution ensures maximum protection against cracking, which is common for products made from solid wood. The wooden supports are impregnated and coated with a triple layer of lacquer, which meets the terms and conditions of the EN71/3 Standard (safe for children's toys). The structures are anchored into the ground in steel plates, which are protected against corrosion by hot-dip galvanizing and fixed in a concrete bed. The anchors are fastened to the play unit with bolts and their structure ensures that they are not in direct contact with the ground. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion. The slides are made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The rope bridges and the rope are made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core) and are connected with plastic or aluminium joints. The platforms and the ramp are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The roofs are made from HPL (High-pressure laminate, which is characterised by high colour stability, UV resistance and water resistance). All fastening material is galvanized or stainless steel.

Equipment

4x tower, 2x A-shaped roof, 2x slide, 3x barrier from HDPE, sloping ramp with the rope and HDPE steps, ladder, 2x rope bridge, sloping ramp with steps and metal handles, 2x bridge with a rope railing.

