



UNIVERSAL 4U141KS - silver

Product type 4U-141KS-10

Basic information

Age category	2 - 15 years
Minimum area	8,8 m x 7,3 m
Equipment measurements	4,79 m x 3,78 m x 3,13 m
Free fall height:	1 m
Load capacity:	Not specified
Max. number of users:	Not specified
Fall zone: EN 1177	Grass surface
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

Material

Wooden units - water-proof plywood
 Metal units - structural steel
 Plastic units - HDPE
 Slides - fibreglass
 Ropes and nets - polypropylene with a steel internal core
 Roof - HPL

Finish

Duplex powder coated with coat curing
 Hot-dip galvanizing

Description

The support structure of the tower unit is made of structural steel (metal profile 100 × 100 mm) which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system.

The slides are made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The rope is made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core). The platform and the ramp are made from water-proof plywood designed for external environment or from HDPE should the client require. The roof is made from HPL (High-pressure laminate, which is characterised by high colour stability, UV resistance and water resistance). All fastening material is galvanized or stainless steel.

Equipment

Tower, 3x slide, A-shaped roof, sloping ramp with the rope and HDPE steps.

