



## UNIVERSAL 6U119KW - brown

Product type 6U-119KW-15

### Basic information

Age category	3 - 15 years
Minimum area	8,5 m x 10,5 m
Equipment measurements	5,55 m x 5,85 m x 3,56 m
Free fall height:	1,5 m
Load capacity:	540 kg
Max. number of users:	10
Fall zone: EN 1177	Rubber or gravel, 67 m <sup>2</sup>
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1, 2, 3

### Material

Wooden units - water-proof plywood  
 Metal units - structural steel  
 Plastic units - HDPE  
 Slide - fibreglass  
 Climbing holds - mix of silica sand and epoxy resin

### Finish

Komaxit powder coating  
 Hot-dip galvanizing

### Description

The support structure of the tower unit is made of structural steel (metal profile 100 × 100 mm) which is protected against corrosion by zinc coating, resulting in a very prolonged service life of the workout elements, and coating with baked paint KOMAXIT according to the RAL colour system. All other metallic elements are also zinc coated and treated with baked paint KOMAXIT according to the RAL colour system.

The slide is made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments).

The platform and the vertical climbing wall are made from water-proof plywood designed for external environment or from HDPE should the client require. The climbing holds are made from the mix of silica sand and epoxy resin, which ensures long life, colour preservation as well as skin friendly surface. All fastening material is galvanized or stainless steel.

### Equipment

Tower, slide, roof, vertical climbing wall, ladder, metal beam, 3x barrier from HDPE.

