



UNIVERSAL 4U307KW - brown

Product type 4U-307KW-15

Basic information

| | |
|------------------------------|---------------------------------------|
| Age category | 3 - 15 years |
| Minimum area | 8,5 m x 10 m |
| Equipment measurements | 5,18 m x 6,38 m x 3,63 m |
| Free fall height: | 1,5 m |
| Load capacity: | 1134 kg |
| Max. number of users: | 21 |
| Fall zone: EN 1177 | Rubber or gravel, 71,5 m ² |
| Designation: | exterior |
| Availability of spare parts: | supplied by the |
| Certificate of Compliance: | ČSN EN 1176 - 1, 2, 3 |

Material

| |
|---|
| Platform - HPL |
| Metal units - stainless steel |
| Ropes and nets - polypropylene with a steel internal core |
| Plastic parts - HDPE, polyamide |
| Slides - fibreglass |
| Tunnel - fibreglass |
| Roof - HPL |

Finish

| |
|---------------------------------------|
| Duplex powder coated with coat curing |
| Hot-dip galvanizing |

Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slides are made from fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The rope bridge and the climbing net are made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core) and are connected with plastic or aluminium joints. The platforms are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The crawler tunnel is made of fibreglass with high UV stability and high colour stability. The roof is made from HPL (High-pressure laminate, which is characterised by high colour stability, UV resistance and water resistance). All fastening material is galvanized or stainless steel.

Equipment

3x tower, 2x slide, A-shaped roof, rope bridge, ladder, 3x barrier from HDPE, crawl tunnel between the towers, sloping net access, sloping ramp with steps and metal handles.

