



## UNIVERSAL 4U308KS - silver

Product type 4U-308KS-15

### Basic information

|                              |                                     |
|------------------------------|-------------------------------------|
| Age category                 | 3 - 15 years                        |
| Minimum area                 | 10 m x 8,5 m                        |
| Equipment measurements       | 6,6 m x 4,9 m x 3,17 m              |
| Free fall height:            | 1,5 m                               |
| Load capacity:               | Not specified                       |
| Max. number of users:        | Not specified                       |
| Fall zone: EN 1177           | Rubber or gravel, 61 m <sup>2</sup> |
| Designation:                 | exterior                            |
| Availability of spare parts: | supplied by the                     |
| Certificate of Compliance:   | ČSN EN 1176 - 1, 2, 3               |

### Material

Platform - HPL  
 Metal units - structural steel  
 Plastic units - HDPE, polyamide  
 Slide - fibreglass  
 Ropes and nets - polypropylene with a steel internal core  
 Climbing holds - mix of silica sand and epoxy resin  
 Tunnel - fibreglass

### Finish

Duplex powder coated with coat curing  
 Hot-dip galvanizing

### Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slide is made from triple-layered fibreglass. The surfaces of the slides, steps, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The climbing net and the rope are made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core) and are connected with plastic or aluminium joints. The platforms, ramp and the sloping climbing wall are made from HPL (High-pressure laminate, which is characterised by high colour stability and water resistance). The climbing holds are made from the mix of silica sand and epoxy resin, which ensures long life, colour preservation as well as skin friendly surface. The crawler tunnel is made of fibreglass with high UV stability and high colour stability. All fastening material is galvanized or stainless steel.

### Equipment

3x tower, slide, 3x barrier made from HDPE, crawl tunnel between the towers, sloping net access, sloping ramp with the rope and HDPE steps, sloping climbing wall, sloping ramp with steps and metal handles.

