



Climbing wall LS301KR - red

Product type LS-301KR-25-Q

Basic information

Age category	3 - 15 years
Minimum area	6 m x 5 m
Equipment measurements	2,67 m x 0,98 m x 2,42 m
Free fall height:	2,5 m
Load capacity:	324 kg
Max. number of users:	6
Fall zone: EN 1177	Rubber or gravel, 30 m ²
Designation:	exterior
Availability of spare parts:	supplied by the
Certificate of Compliance:	ČSN EN 1176 - 1

Material

Wooden units - water-proof plywood
 Metal units - structural steel
 Climbing holds - mix of silica sand and epoxy resin

Finish

Duplex powder coated with coat curing
 Hot-dip galvanizing

Description

The support structure of the climbing wall is made from structural steel (steel profile 100 x 100 mm), it is zinc coated which significantly prolongs the life of the play unit and KOMAXIT powder coated according to the RAL colour chart. The structure is fixed in a concrete bed. All other metal units are zinc coated and KOMAXIT powder coated according to the RAL.

The climbing wall is made from water-proof plywood designed for external use. The climbing holds are made from the mix of silica sand and epoxy resin, which ensures long life, colour preservation as well as skin friendly surface. All fastening material is galvanized or stainless steel.

Equipment

We offer three color variants of the support structure - red, blue and brown.

