



## UNIVERSAL 4U259KW-B - brown

Product type 4U-259KW-10-B

### Basic information

|                              |                          |
|------------------------------|--------------------------|
| Age category                 | 1 - 10 years             |
| Minimum area                 | 7,67 m x 8,5 m           |
| Equipment measurements       | 3,48 m x 5,01 m x 2,41 m |
| Free fall height:            | 0.6 m                    |
| Load capacity:               | 594 kg                   |
| Max. number of users:        | 11                       |
| Fall zone: EN 1177           | Grass surface            |
| Designation:                 | exterior                 |
| Availability of spare parts: | supplied by the          |
| Certificate of Compliance:   | ČSN EN 1176 - 1, 2, 3    |

### Material

Metal parts - structural steel  
 Plastic parts - HDPE, polyamide  
 Slide - fibreglass  
 Ropes and nets - polypropylene with a steel internal core  
 Platforms - HPL  
 Apertures - Plexiglass  
 Seat - rubber with an aluminum insert

### Finish

Duplex powder coated with coat curing  
 Hot-dip galvanizing

### Description

The support structure of the tower unit is made of structural steel which is protected against corrosion by zinc coating, resulting in a very prolonged service life or duplex powder coated with coat curing according to RAL to prevent corrosion. All other metallic elements are also zinc coated or duplex powder coated with coat curing according to RAL to prevent corrosion.

The slide is made from fibreglass. The surfaces of the slides, barriers, etc. are made from high quality HDPE plastic (high density coloured polyethylene, which is characterised by high colour stability, UV resistance but mainly safety as it doesn't break and therefore there is no danger of injury to children by sharp fragments). The rope bridge is made using HERKULES material (16 mm thick ropes made from polypropylene with a steel internal core) and are connected with plastic or aluminium joints. The platform and the ramp are made from HPL (High-pressure laminate, which is characterised by high colour stability, UV resistance and water resistance). The swing is hung on a metal girder using galvanized chains. The seat is made of rubber and is reinforced with an aluminum insert. The chains are stainless steel, resulting in a very prolonged service life of the product. All fastening material is stainless steel.

### Equipment

2x Tower, slide, roof in the shape of a leaf, sloping ramp with steps and HDPE handles, sloping ramp with HDPE steps, 2x barrier, rope bridge, barrier with an aperture, BABY seat.

